

Identifiant de connexion simplifié



Cette page n'est plus actualisée. À partir de BlueMind 4.8, veuillez consulter la [nouvelle documentation BlueMind](#)

Présentation

Afin de permettre aux utilisateurs de saisir simplement leur nom d'utilisateur, sans la partie domaine, lors de la connexion à BlueMind (par exemple "jdoe" au lieu de "jdoe@bluemind.loc") il suffit de configurer un domaine par défaut sur le serveur.



Autres domaines

Lorsque cette configuration est en place, il est toujours possible de se connecter sur un autre domaine. Il faut alors indiquer le domaine complet (exemple : jdoe@yellowmind.loc).

Mise en œuvre

- éditer le fichier `/etc/bm/bm.ini` et rajouter à la fin la ligne suivante :

```
default-domain=bluemind.loc
```

NB : remplacer bluemind.loc par le nom du domaine concerné

- redémarrer le service bm-hps :

```
service bm-hps restart
```

La page d'identification se présente alors ainsi :

The screenshot shows the BlueMind login page with a dark blue background. In the top left is the BlueMind logo. In the top right is a circular icon containing a hexagon and a person silhouette. Below these are two input fields: 'Identifiant' with the text 'jdoe' and a dropdown menu showing '@bluemind.loc', and 'Mot de passe' with four dots. Below the password field are two radio buttons: 'Ordinateur privé' (selected) and 'Ordinateur public'. At the bottom center is a large blue button labeled 'SE CONNECTER'. Below the button is the version number '3.5.5'.